

Bolt on Tapping Saddles

PN10	Size OD (mm)	Code	Outlet	Weight (kg)
1 	50	BTS5025	1" (25 mm)	0.188
	63	BTS6325	1" (25 mm)	0.288
	63	BTS6340	1½" (40 mm)	0.322
	75	BTS7525	1" (25 mm)	0.376
	75	BTS7540	1½" (40 mm)	0.409
	75	BTS7550	2" (50 mm)	0.433
	90	BTS9025	1" (25 mm)	0.461
	90	BTS9040	1½" (40 mm)	0.494
2 	90	BTS9050	2" (50 mm)	0.511
	110	BTS11025	1" (25 mm)	0.568
	110	BTS11040	1½" (40 mm)	0.599
	110	BTS11050	2" (50 mm)	0.615
	125	BTS12550	2" (50 mm)	0.797
	140	BTS14050	2" (50 mm)	0.938
	160	BTS16025	1" (25 mm)	1.089
	160	BTS16040	1½" (40 mm)	1.071
	160	BTS16050 (1)	2" (50 mm)	1.080
	160	BTS16080	3" (80 mm)	-
	160	BTS160100	4" (100 mm)	-
	180	BTS18050	2" (50 mm)	-
	200	BTS20050	2" (50 mm)	-
	200	BTS20080	3" (80 mm)	-
	200	BTS200100	4" (100 mm)	-
	225	BTS22550	2" (50 mm)	-
	225	BTS22580	3" (80 mm)	-
	225	BTS225100	4" (100 mm)	-
	250	BTS25050	2" (50 mm)	-
	250	BTS25080	3" (80 mm)	-
	250	BTS250100	4" (100 mm)	-
	280	BTS28050 (2)	2" (50 mm)	-
	280	BTS28080	3" (80 mm)	-
	280	BTS280100	4" (100 mm)	-
	315	BTS31550	2" (50 mm)	-
	315	BTS31580	3" (80 mm)	-
	315	BTS315100	4" (100 mm)	-